

# ROBUSTnode™

Featuring Intel Xeon E5-2600 V3 and DDR4 memory, Robust™ packed super computing power into compact 1U (14" depth) and high dense 4-nodes-in-2U form factor that support up to 8x processors. Robust™ render node series is an excellent choice that excel in performance, rack space and total cost of ownership which offers high ROI.



## System Integration

Robust™ provides on-demand render manager integration and consulting session for our customers, an one stop solution to our customers in which they could fully utilize the hardware in order to push their productivity beyond the limit.

## Key features of ROBUSTnode™ include:

- **High performance.** Using an inappropriate processor could lead to really slow render. Robust team assembles and configures ROBUSTnode™ after careful and thorough study of user's usage pattern to ensure high performance is being delivered.
- **Highly Customizable.** Unlike convention 1U/2U server, ROBUSTnode™ is highly customizable. For instance, choice of 7200/15K RPM HDD or SSD, wide range of processors, etc.
- **Centralized Monitoring and Remote Management.** With IPMI, users can manage the node remotely. Getting health status, fan speed, power on/off can all be done from user's desktop.
- **Reliability.** All components are fully tested to ensure 24/7 operation.

## Sample Configuration

The flexibility and scalability of ROBUSTnode 4-in-2U demonstrated in the below reference configuration:

